# **WR574**





### **5G Industrial Router**

WR574 is a cellular industrial router providing 5G/4G/3G access. It supports 4 GE ports and Wi-Fi 6. With WAN failover, WR574 is able to provide stable Gigabit-class access for Ethernet equipments.









**5G NSA&SA** 

Wi-Fi 6 AX1800

4 x GE ports

**WAN Failover** 





#### **KEY FEATURES**

- 3\*GE +1\*PoE-PD GE + Wi-Fi + 5G
- 3GPP Rel-16 Complied, support sub-6GHz NSA and SA mode
- IEEE 802.11 a/b/g/n/ac
- WAN failover between ETH WAN and Cellular WAN
- VPN: PPTP, L2TP, IPSec, GRE, OpenVPN, WireGuard
- BGP, OSPF, RIP, NHRP, VRRP
- Modbus, MQTT
- Management: Web GUI, SSH, TR069, SNMP, SMS, RMS







## **SPECIFICATIONS**

# wavetel

#### **Hardware**

Ethernet 4\*10/100/1000Mbps Port

Cellular 5G NR

Wi-Fi Wi-Fi 6 AX1800; 2.4GHz 2\*2, 5.8GHz 2\*2

Serial Port -

I/O 1\*DI

PoE Active PoE PD

Antenna 2\*RP-SMA Wi-Fi Antenna

4\*SMA Cellular Antenna

1\* GNSS SMA

Sim Card Slot 2\*4FF
GNSS Yes

LED Power, System, Wi-Fi, Cellular, Signal Strength

Power 4-Pin Molex

Reset Button 1
Grounding Screw 1

Housing Material Aluminium Ingress Protection IP30 Weight 320g

Size 114\*88\*40mm Operating temperature -40 C ~75 C

Operating humidity 10% to 90% non-condensing Installation Desktop, Wall-mounted, Din-rail

#### **Software**

Network Multi-WAN: ETH WAN, Cellular WAN

WAN Failover, Load Balancing

Protocols PPPoE, TCP, UDP, DHCP, NAT, DNS, NTP, SMTP, Telnet,ICMP, HTTPS, TLS, ARP, VLAN, SSH2, DDNS

Cellular 5G Sub-6GHz, NSA&SA Mode

SMS, Dual-APN, Band Lock, PIN Management, IP Passthrough

Sim auto-switch

Wi-Fi Standard: IEEE 802.11 a/b/g/n/ac/ax; Speed: WiFi AX1800; Frequency: 2.4GHz and 5GHz

Channel Bandwidth: 20MHz/40MHz/80MHz Security: WEP, WPA-PSK, WPA2-PSK, WPA3

Encription: AES, TKIP Wi-Fi Users: Up to 48 Users

Whitelist, Blacklist"

VPN PPTP, L2TP, IPSec, GRE, OpenVPN, WireGuard

MQTT Broker, MQTT Publisher

MQTT Gateway
Data to Server

Modbus Supported Mode: Server, Client

Supported Types: TCP

Supporetd Data Formats:8-bit INT / UINT, 16-bit INT / UINT, 32-bit float / INT / UINT, HEX, ASCII

Routing Static Route, Policy Route, BGP, OSPF, RIP, NHRP, VRRP

Security Firewall, DMZ, Anti-DDOS, Website Filtering, Access Control, 802.1x

Device Management Web GUI, SSH, TR069, SNMP, SMS, RMS



